



产品符号	主体材质	锁定螺母
PLLX-A	钢	无*1
PLLX-AK	钢	有
PLLXS-A	不锈钢	无*1
PLLXS-AK	不锈钢	有

型号 钢制	B	s	M(细牙)		D	D ₁	L	L ₁	L ₂	L _b	sw	sw ₁	载荷(N) min./max.	销的 剪切载荷(N)	适用轴环	质量(g)
			螺纹公称直径	螺距											PXCS → P.xxxx	
PLLX-4-4-A	4	4	M8	1	16	11.5	42	16	5	—	10	—	4.5 / 12	1120	PXCS-8-10-**	12
PLLX-4-6-A	4	6	M8	1	16	11.5	42	16	5	—	10	—	4 / 12.5	1120	PXCS-8-10-**	12
PLLX-5-5-A	5	5	M10	1	19	13.8	48	18	6	—	12	—	5 / 15	1750	PXCS-10-12-**	21
PLLX-5-8-A	5	8	M10	1	19	13.8	48	18	6	—	12	—	5 / 18	1750	PXCS-10-12-**	21
PLLX-6-6-A	6	6	M12	1.5	23	16.2	58	22	6	—	14	—	6.5 / 19	2530	PXCS-12-14-**	33
PLLX-6-9-A	6	9	M12	1.5	23	16.2	58	22	6	—	14	—	6 / 25	2530	PXCS-12-14-**	34
PLLX-8-8-A	8	8	M16	1.5	28	19.6	70	26	8	—	17	—	8.5 / 26	4500	PXCS-16-17-**	68
PLLX-8-12-A	8	12	M16	1.5	28	19.6	70	26	8	—	17	—	8.5 / 28	4500	PXCS-16-17-**	69
PLLX-10-12-A	10	12	M16	1.5	28	19.6	70	26	8	—	17	—	9.5 / 38	7030	PXCS-16-17-**	70
PLLX-12-15-A	12	15	M20	1.5	28	25.4	79	33	10	—	22	—	11.5 / 40	10100	PXCS-20-22-**	131
PLLX-4-4-AK	4	4	M8	1	16	11.5	42	16	5	4	10	13	4.5 / 12	1120	PXCS-8-10-**	17
PLLX-4-6-AK	4	6	M8	1	16	11.5	42	16	5	4	10	13	4 / 12.5	1120	PXCS-8-10-**	17
PLLX-5-5-AK	5	5	M10	1	19	13.8	48	18	6	5	12	17	5 / 15	1750	PXCS-10-12-**	28
PLLX-5-8-AK	5	8	M10	1	19	13.8	48	18	6	5	12	17	5 / 18	1750	PXCS-10-12-**	28
PLLX-6-6-AK	6	6	M12	1.5	23	16.2	58	22	6	6	14	18	6.5 / 19	2530	PXCS-12-14-**	43
PLLX-6-9-AK	6	9	M12	1.5	23	16.2	58	22	6	6	14	18	6 / 25	2530	PXCS-12-14-**	44
PLLX-8-8-AK	8	8	M16	1.5	28	19.6	70	26	8	8	17	24	8.5 / 26	4500	PXCS-16-17-**	88
PLLX-8-12-AK	8	12	M16	1.5	28	19.6	70	26	8	8	17	24	8.5 / 28	4500	PXCS-16-17-**	89
PLLX-10-12-AK	10	12	M16	1.5	28	19.6	70	26	8	8	17	24	9.5 / 38	7030	PXCS-16-17-**	105
PLLX-12-15-AK	12	15	M20	1.5	28	25.4	79	33	10	10	22	30	11.5 / 40	10100	PXCS-20-22-**	166

	PLLX-A	PLLX-AK	PLLXS-A	PLLXS-AK
旋钮	尼龙6(亚光黑)	尼龙6(亚光黑)	尼龙6(亚光黑)	尼龙6(亚光黑)
主体	SUM22L 四氧化三铁保护膜(黑)	SUM22L 四氧化三铁保护膜(黑)	SUS303	SUS303
销	S45C(硬度50-60HRC)	S45C(硬度50-60HRC)	SUS303 镀镍	SUS303 镀镍
弹簧	SWPB	SWPB	SUS301	SUS301
锁定螺母		S45C 四氧化三铁保护膜(黑)		SUS303

型号 不锈钢制	B 	s 	M(细牙) 螺纹公称直径	螺距	D	D1	L	L1	L2	Lb	sw	sw1	载荷(N) min./max.	销的 剪切载荷(N)	适用轴环  P.xxxx	质量(g)
PLLXS-4-4-A	4	4	M8	1	16	11.5	42	16	5	—	10	—	4.5 / 12	1160	PXCS-8-10-**	12
PLLXS-4-6-A	4	6	M8	1	16	11.5	42	16	5	—	10	—	4 / 12.5	1160	PXCS-8-10-**	12
PLLXS-5-5-A	5	5	M10	1	19	13.8	48	18	6	—	12	—	5 / 15	1820	PXCS-10-12-**	21
PLLXS-5-8-A	5	8	M10	1	19	13.8	48	18	6	—	12	—	5 / 18	1820	PXCS-10-12-**	21
PLLXS-6-6-A	6	6	M12	1.5	23	16.2	58	22	6	—	14	—	6.5 / 19	2620	PXCS-12-14-**	33
PLLXS-6-9-A	6	9	M12	1.5	23	16.2	58	22	6	—	14	—	6 / 25	2620	PXCS-12-14-**	34
PLLXS-8-8-A	8	8	M16	1.5	28	19.6	70	26	8	—	17	—	8.5 / 26	4660	PXCS-16-17-**	68
PLLXS-8-12-A	8	12	M16	1.5	28	19.6	70	26	8	—	17	—	8.5 / 28	4660	PXCS-16-17-**	69
PLLXS-10-12-A	10	12	M16	1.5	28	19.6	70	26	8	—	17	—	9.5 / 38	7280	PXCS-16-17-**	70
PLLXS-12-15-A	12	15	M20	1.5	28	25.4	79	33	10	—	22	—	11.5 / 40	10400	PXCS-20-22-**	131
PLLXS-4-4-AK	4	4	M8	1	16	11.5	42	16	5	4	10	13	4.5 / 12	1160	PXCS-8-10-**	17
PLLXS-4-6-AK	4	6	M8	1	16	11.5	42	16	5	4	10	13	4 / 12.5	1160	PXCS-8-10-**	17
PLLXS-5-5-AK	5	5	M10	1	19	13.8	48	18	6	5	12	17	5 / 15	1820	PXCS-10-12-**	28
PLLXS-5-8-AK	5	8	M10	1	19	13.8	48	18	6	5	12	17	5 / 18	1820	PXCS-10-12-**	28
PLLXS-6-6-AK	6	6	M12	1.5	23	16.2	58	22	6	6	14	18	6.5 / 19	2620	PXCS-12-14-**	43
PLLXS-6-9-AK	6	9	M12	1.5	23	16.2	58	22	6	6	14	18	6 / 25	2620	PXCS-12-14-**	44
PLLXS-8-8-AK	8	8	M16	1.5	28	19.6	70	26	8	8	17	24	8.5 / 26	4660	PXCS-16-17-**	88
PLLXS-8-12-AK	8	12	M16	1.5	28	19.6	70	26	8	8	17	24	8.5 / 28	4660	PXCS-16-17-**	89
PLLXS-10-12-AK	10	12	M16	1.5	28	19.6	70	26	8	8	17	24	9.5 / 38	7280	PXCS-16-17-**	105
PLLXS-12-15-AK	12	15	M20	1.5	28	25.4	79	33	10	10	22	30	11.5 / 40	10400	PXCS-20-22-**	166



PLLXS-8-12-AK